

NCR SelfServ™ 16

Compact Interior Freestanding Cash Dispenser

Looking for a reliable ATM with flexible placement opportunities?

YES

Connect with more customers in more locations

The NCR SelfServ 16 is a small footprint, free-standing, interior cash dispenser that offers a very low total cost of ownership. Ideal for large independent depolyers or banks looking to deploy in off-premise locations or in bank branches, the intuitively designed NCR SelfServ 16 will attract customers and handle even the highest transaction volumes. At the same time, the compact footprint provides maximum placement flexibility where floor space is at a premium.

- **Redefined availability**

Real availability is about delivering the transactions that consumers want, where and when they need them. Built around our proven and reliable spray dispense technology, the SelfServ 16 is capable of handling low to high transaction volumes. With it's compact footprint the SelfServ 16 can be deployed into a broader range of locations, successfully serving more customers.

- **Informed manageability**

The SelfServ 16 is suitable for both CIT and merchant fill environments. With minimal infrastructure requirements the SelfServ 16 is easy to install, manage and maintain. It's front access design ensures that cash replenishment is fast and easy.

- **Committed responsibility**

A range of high-performance core processors, low-energy LED lighting and fixed length receipts are just some of the ways we've reduced the carbon footprint of the NCR SelfServ 16, making it a valuable asset in both achieving the environmental goals for your business and reducing total cost of ownership.

- **Intuitive usability**

With fresh and modern styling, a large 15" LCD display, a compact user interface and a simple module layout the SelfServ 16 ensures that consumers and staff become experts after their very first use, resulting in better consumer satisfaction, operational efficiency and staff productivity.

- **Intrinsic security**

Incorporating a range of anti-fraud and physical security solutions—NCR SelfServ 16 reduces fraud risk and maintains the integrity of your self-service channel for you and your customers.



For more information, visit www.ncr.com, or email financial@ncr.com.

Key Features

- Fully recessed PCI compliant Encrypting PIN Pad
- Intuitive low-power media entry and exit indicators
- High-capacity, spray dispenser
- 15" LCD with touchscreen option
- Card reader with built-in fraud prevention
- Low-power, high-performance entry level core processor

Why NCR?

With over 125 years of experience and knowledge, NCR is a leading global provider of payments, assisted- and self-service solutions. NCR has been the global number one manufacturer of ATMs for more than 22 consecutive years. We help our clients around the world improve their customer interactions, implement change quickly and proactively, and transform their businesses to become leaders and change agents. We can help you, too.

Technical Specifications

PRODUCT DIMENSIONS

- HEIGHT 55.6" (1,412mm)
- WIDTH 17.7" (450mm)
- DEPTH 24.9" (633mm)
- WEIGHT 485lbs (220kg)

CONSUMER INTERFACE

- Display – Choice of 15" LCD color with 8 FDKs or 15" LCD touchscreen, XGA with autoscaling, optional privacy filter, sunlight readable displays
- Keyboard – Full recessed EPP (PCI compliant), polycarbonate or stainless steel
- Card Reader – Dip card reader, Smart Dip card reader, Smart IMCRW with CROPF and/or System Escape, HiCo
- Optional Integrated Media Entry and Exit Indicators (MEEI)
- Audio - Optional high quality public audio and/or sound jack with volume control
- Barcode Reader - 2D Barcode supports both 1D and 2D documents

DISPENSER

- 1 to 3 cassettes, spray dispenser

PRINTERS

- Receipt Printer - 80mm 203dpi graphics thermal printer
- Journal Printer - 80mm 203dpi graphics thermal printer (option)

SECURITY

- Enhanced Card Drive. Options – Fraudulent Device Inhibitor (FDI), Solidcore Suite for APTRA, Camera enabled facility
- UL Business Hours safe

COMMUNICATION OPTIONS

- Dial-up, TCP/IP, Leased line, Wireless communications-enabled, Integrated Ethernet

ENVIRONMENTAL

- Temperature - 50°F to 104°F (10°C to 40°C)
- Humidity - 20% to 80%
- Acoustics - Sound power 65db (A) idle, 68db(A) operating

SOFTWARE

- Windows® XP Pro
- XFS 5.01.00 or later
- NCR APTRA software suite



Experience a new world of interaction

NCR SelfServ 16

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR SelfServ and NCR APTRA are either registered trademarks or trademarks of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2010 NCR Corporation Patents Pending

EB10325-1110

www.ncr.com