



NCR EasyPoint™ 57

Specification

MORE ↗ **RESULTS**

Product dimensions	
Height	57.7" (1,465mm)
Width	18.5" (470mm)
Depth	26.3" (668mm)
Weight Business hours	319lbs (145kg) (1 high)
Installation	Suitable for interior locations

Customer interface

Display

7.7" (196mm) VGA color flat panel screen

8 tactile function display keys

Keyboard

Secure EPP (Encrypting PIN Pad): supports Triple DES and Remote Key Management

Card reader

DIP

Smart DIP: supports smart cards

Dispenser

1-2 cassettes

Printer

Receipt printer

40 column graphics thermal

Capacity up to 2,500 transactions, 4.4" (112mm) receipts

Security

EPP (Encrypting PIN Pad): certified as meeting the requirements of ISO 9564-1, ISO 13491-1, and ISO 13491-2

* Where available

Smart DIP card reader: certified to EMV 3.1.1 Level 1

Safes

Business hours

UL291 Level 1 enclosure

Accessibility

Subject to customer compliance with NCR Site Preparation and Installation Guidelines, the EasyPoint 57 complies with **ADAAG sections 4.34.2, 4.34.3 and 4.34.4** (as amended through September 2002). Of the remaining portions of ADAAG specifically addressed to automated teller machines, section 4.34.1 addresses the route on which the product is placed and not aspects of the product itself and section 4.34.5 is a performance standard that does not specify how to achieve or measure compliance and therefore NCR does not offer guidance as to such compliance.

• **AS3769-1990 - Australian Standard for Accessibility** - with minor exceptions, the EasyPoint 57 complies with this standard

• **Access to ATMs: UK Design Guidelines 2002** - with minor exceptions, the EasyPoint 57 conforms with these guidelines

• **CAN/CSA B651.1-01** - with minor exceptions, the EasyPoint 57 complies with this standard

Additional features

Electronic journaling

Revenue generation options

Back-lit advertising/logo panel

iATMglobal capable

Communication options

Visa II dial-up

TCP/IP

Leased line

56k V. 90 internal modem

Wireless communications enabled*

Environmental

Temperature

50°F to 104°F (10°C to 40°C)

Humidity

20% to 80%

Acoustics

Sound power 55dBA idle, 60dBA operating

Sound pressure 55dBA operating

Power requirements

120v to 240v
50Hz to 60Hz

Electronic platform

PC based with option of Celeron or Pentium® III processors

Software

Windows® XP and OS/2

APTRA™ software suite

Encrypting PIN Pad



Smart DIP card reader



Advertising/logo panel



APTRA enabled



NCR Corporation, 1700 South Patterson Boulevard, Dayton, Ohio, 45479, USA

www.ncr.com

www.self-service-touchpoints.com

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

© 2004 NCR Corporation

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

SP 7918